

G-80095BG

Galileo[®]



1564 - 1642

Instructions

G-80095BG

FOR ADDITIONAL HELP
PLEASE VISIT:



WWW.COSMOSOPTICS.COM

IF YOU NEED ANY FURTHER HELP WITH YOUR GALILEO TELESCOPE
PLEASE CALL US @ 305-245-8444 MON-FRI 9AM - 5PM E.S.T
OR E-MAIL US AT CUSTOMERSERVICE@COSMOSOPTICS.COM

GALILEO G-80095BG OPERATING INSTRUCTIONS

INTRODUCTION

THIS TELESCOPE HAS BEEN PRODUCED TO PRECISE SPECIFICATIONS.

PRIOR TO USING YOUR NEW GALILEO TELESCOPE, PLEASE READ THE FOLLOWING SETUP AND USAGE INSTRUCTIONS. IT IS IMPORTANT TO PROPERLY ASSEMBLE YOUR TELESCOPE IN ORDER TO ALLOW IT TO FUNCTION PROPERLY.

USE THE TELESCOPE FOR TERRESTRIAL (LAND) VIEWING BEFORE ATTEMPTING TO VIEW ASTRONOMICAL OBJECTS. THIS WILL FAMILIARIZE YOU WITH HOW POWERFUL EACH EYEPIECE WILL BE, AS WELL AS INTRODUCE YOU TO THE FUNCTIONS OF YOUR ACCESSORY LENSES.

THE IMAGE YOU SEE WILL BE UPSIDE DOWN AND BACKWARD. THIS IS DUE TO THE FACT THAT YOUR TELESCOPE IS AN ASTRONOMICAL TELESCOPE AND HAS BEEN MANUFACTURED FOR ASTRONOMICAL OBSERVATIONS. IN ASTRONOMICAL VIEWING, THERE IS NO UP OR DOWN, NO RIGHT OR LEFT.

WE RECOMMEND YOU BEGIN WITH THE LOWEST POWER EYEPIECE, 20MM WHEN USING YOUR TELESCOPE. AS YOU INCREASE THE POWER TO 6MM YOUR POWER WILL BE HIGHER, BUT THE IMAGE WILL APPEAR DARKER. THIS IS DUE TO THE BASIC PHYSICAL PROPERTIES OF THE TELESCOPE. THE HIGHER THE POWER YOU USE, THE DARKER THE IMAGE WILL APPEAR AND YOUR VIEWING FIELD WILL BE MORE NARROW.

PLEASE BE PATIENT WHEN USING YOUR TELESCOPE. IT IS A VERY SENSITIVE INSTRUMENT THAT IS CAPABLE OF USING HIGH POWER. HOWEVER, THE MORE POWER YOU USE, THE MORE SENSITIVE THE TELESCOPE BECOMES. AS A RESULT THE SLIGHTEST MOVEMENT OF THE TELESCOPE COULD CAUSE YOU TO LOSE THE IMAGE YOU HAVE IN YOUR EYEPIECE. PRACTICE WILL ENABLE YOU TO KNOW HOW MUCH MOVEMENT TO EXPECT WITH EACH EYEPIECE AND IT'S CORRESPONDING POWER.

**IF YOU NEED ANY FURTHER HELP WITH YOUR GALILEO TELESCOPE
PLEASE CALL US @ 305-245-8444 MON-FRI 9AM - 5PM E.S.T
OR E-MAIL US AT CUSTOMERSERVICE@COSMOSOPTICS.COM**

ACCESSORIES

- A. FULLY ADJUSTABLE TRIPOD



- B. EYEPIECES

20MM EYEPIECE =40X (LEAST POWERFUL - MOST LIGHT)
6MM EYEPIECE =133X (MOST POWERFUL - LEAST LIGHT)




- C. 3X BARLOW.

USED TO INCREASE THE POWER OF ANY GIVEN EYEPIECE BY 300%. FOR EXAMPLE THE 20MM IS 40X POWER AND WITH THE 3X BARLOW IT IS 120X POWER.



- D. MARS-EYE ELECTRONIC FINDER:

USED TO LOCATE OBJECTS PRIOR TO USING MAIN TELESCOPE.
PLEASE NOTE YOU MUST ALIGN THE FINDER WITH THE MAIN TUBE PRIOR TO INITIAL ASTRONOMICAL OR TERRESTRIAL USE.



- E. 1.25 INCH HELICAL RACK & PINION FOCUSER.
ALLOWS FOR PRECISE FOCUSING.



- F. GALILEO STELLARIUM CD-ROM
FROM ANY LOCATION YOU CAN SEE THE SKY AS IT APPEARS AT ANY TIME OF DAY, OR EVEN IN THE FUTURE.



**IF YOU NEED ANY FURTHER HELP WITH YOUR GALILEO TELESCOPE
PLEASE CALL US @ 305-245-8444 MON-FRI 9AM - 5PM E.S.T
OR E-MAIL US AT CUSTOMERSERVICE@COSMOSOPTICS.COM**

GALILEO G-80095BG ASSEMBLY INSTRUCTIONS

CAUTION: NEVER POINT YOUR TELESCOPE AT THE SUN. VIEWING THE SUN WITH THIS TELESCOPE OR EVEN THE UNAIDED EYE CAN RESULT IN BLINDNESS OR OTHER SERIOUS EYE DAMAGE.

1. REMOVE PRE-ASSEMBLED TRIPOD
2. ADJUST TRIPOD TO PROPER HEIGHT BY LOOSENING, ADJUSTING AND TIGHTENING THE LOCKING KNOBS.





3. REMOVE TELESCOPE AND MOUNT FROM CARTON.
NOTE: THEY COME PRE-ASSEMBLED FROM THE FACTORY.
4. LOOSEN MOUNTING KNOB ON THE TELESCOPE MOUNT (UNDERNEATH)



5. PLACE THE TELESCOPE AND MOUNT ASSEMBLY ONTO THE TOP OF THE TRIPOD.
6. TIGHTEN LOCKING KNOB (UNDERNEATH THE TRIPOD TOP) SECURELY.



7. ATTACH ACCESSORY TRAY



ACCESSORY TRAY

- (1) SPREAD TRIPOD LEGS APART SO THE TRAY WILL FIT UNDERNEATH
- (2) PLACE THE TRAY'S HOOK OVER THE HOLDER'S METAL ROD AND PUSH DOWN
- (3) TIGHTEN THE HOLDER'S LOCKING KNOB TO HOLD THE ACCESSORY TRAY IN PLACE

IF YOU NEED ANY FURTHER HELP WITH YOUR GALILEO TELESCOPE
PLEASE CALL US @ 305-245-8444 MON-FRI 9AM - 5PM E.S.T
OR E-MAIL US AT CUSTOMERSERVICE@COSMOSOPTICS.COM

8. LOOSEN SCREWS ON MARS-EYE ELECTRONIC FINDER AND SLIDE ONTO BRACKET. TIGHTEN ATTACHMENT SCREWS.



(PLEASE SEE FURTHER INSTRUCTIONS ON MARS-EYE FINDER).

9. REMOVE CAPS WHEN TELESCOPE IS IN USE, AND REPLACE WHEN NOT IN USE. THIS WILL KEEP THE TELESCOPE'S OPTICS CLEAN.



10. THE COLLIMATION SPOT ON THE PRIMARY MIRROR IS FOR THE OPTICAL ALIGNMENT OF THE TELESCOPE, AND IS NOT A DEFECT.



FEATURES OF G-80095BG



HOW TO USE EYEPIECES & ACCESSORIES

PROPER PLACEMENT OF THE EYEPIECES AND ACCESSORIES ARE IMPORTANT IN ORDER TO ASSURE EASY OPERATIONS AND CLEAR VIEWING.

PLEASE CONSIDER USING YOUR ACCESSORIES IN THE FOLLOWING ORDER. BY DOING THIS YOU WILL BETTER UNDERSTAND THE IMPACT EACH INDIVIDUAL ACCESSORY HAS ON THE FUNCTION OF YOUR TELESCOPE.



1. FOCUSING TUBE - TURN FOCUSING WHEELS TOWARD THE TELESCOPE UNTIL IT WILL GO NO FURTHER. TO FOCUS BEGIN TO TURN THE FOCUSING KNOBS TOWARD YOUR BODY SLOWLY, UNTIL THE IMAGE IS CLEAR. NOTE: YOU MUST HAVE AN EYEPIECE INSERTED IN ORDER TO VIEW IMAGE. PLEASE READ FURTHER.



2. EYEPIECE INSERTION - INSERT AN EYEPIECE INTO THE RECEIVING END OF THE FOCUSING TUBE. WE SUGGEST YOU ALWAYS BEGIN WITH THE LOWEST POWER EYEPIECE (20MM). THE LOWER THE NUMBER ON THE EYEPIECE, THE HIGHER THE POWER YOUR TELESCOPE WILL BE USING. ALSO AS YOU INCREASE YOUR POWER YOU WILL DECREASE THE FIELD OF VIEW AND THE BRIGHTNESS OF YOUR TELESCOPE. WE SUGGEST YOU ALWAYS USE THE LOWEST POWER REQUIRED TO VIEW YOUR SUBJECT.



3. BARLOW LENS - THE BARLOW LENS IS USED TO ACHIEVE THE MAXIMUM POWER FROM YOUR TELESCOPE. INSERT THE BARLOW DIRECTLY INTO THE FOCUSING HOUSING, THEN INSERT AN EYEPIECE INTO THE RECEIVING END OF YOUR BARLOW LENS. REMEMBER YOU WILL HAVE TO READJUST YOUR FOCUSING DUE TO THE FACT THAT YOU HAVE INCREASED THE POWER OF YOUR TELESCOPE.

20MM IDEALLY SUITED FOR ALL TERRESTRIAL AND ASTRONOMICAL VIEWING.
6MM EYEPIECE IS RECOMMENDED FOR NIGHTS OF STEADY SEEING.

**IF YOU NEED ANY FURTHER HELP WITH YOUR GALILEO TELESCOPE
PLEASE CALL US @ 305-245-8444 MON-FRI 9AM - 5PM E.S.T
OR E-MAIL US AT CUSTOMERSERVICE@COSMOSOPTICS.COM**

MARS-EYE ELECTRONIC FINDER MOUNTING & ALIGNMENT

TO MOUNT:

- 1) REMOVE MARS-EYE ELECTRONIC FINDER FROM BOX.
- 2) LOOSEN THUMB SCREWS ON SIDE OF FINDER AND SLIDE FINDER ONTO DOVETAIL MOUNT LOCATED AT TOP OF MAIN TELESCOPE TUBE.
- 3) TIGHTEN THUMB SCREWS.

TO CHECK ALIGNMENT WITH MAIN TELESCOPE:(IMPORTANT!)

- 1) THE MARS-EYE ELECTRONIC FINDER IS NOT PRE-SET AT FACTORY. THE FOLLOWING WILL ALLOW YOU TO ADJUST THE ALIGNMENT.
- 2) DURING THE DAY LIGHT HOURS, AIM THE MAIN TELESCOPE AT AN OBJECT AT LEAST 1/4 MILE OR MORE IN THE DISTANCE AND BRING IT INTO FOCUS.(VERY IMPORTANT)
- 3) ONCE YOU HAVE CENTERED THE REFERENCE ITEM IN THE MAIN TUBE, TIGHTEN ALL KNOBS AND ADJUSTMENTS TO PREVENT ANY MOVEMENT.
- 4) REMOVE CIRCULAR BATTERY SAVER LOCATED BENEATH FRONT OF FINDER (BE SURE TO SAVE AND REPLACE THE BATTERY SAVER WHEN NOT IN USE.)
- 5) TURN FINDER ON BY SLIDING ON/OFF SWITCH FORWARD. ON/OFF SWITCH IS LOCATED ON THE RIGHT SIDE OF THE FINDER.
- 6) LOOK THROUGH THE FINDER AND LOCATE THE RED DOT.



- 7) IF THE OBJECT IN THE MARS-EYE FINDER IS NOT THE OBJECT YOU SEE THROUGH THE MAIN TELESCOPE TUBE, ADJUSTMENT IS REQUIRED.
- 8) TO MOVE THE RED DOT UP AND DOWN, SIMPLY TURN THE ELEVATION SCREW LOCATED ON THE REAR BOTTOM OF THE FINDER TO HEIGHT REQUIRED.
- 9) TO MOVE THE RED DOT LEFT AND RIGHT, SIMPLY TURN THE WINDAGE SCREW LOCATED AT THE FRONT LEFT SIDE OF THE FINDER TO THE PROPER POSITION.
- 10) THESE ADJUSTMENTS WILL ALLOW YOU TO POSITION THE RED DOT ON THE SAME OBJECT CENTERED IN THE MAIN TELESCOPE.



POWER CHART

EYEPIECE	POWER	POWER W/3X BARLOW
6MM	133X	399X
20MM	40X	120X

GETTING THE MOST FROM YOUR TELESCOPE

TAKE THE TIME TO BECOME FAMILIAR WITH YOUR NEW TELESCOPE. LEARN THE NAMES OF THE VARIOUS PARTS, WHERE THEY ARE LOCATED AND THEIR FUNCTION. IT IS BEST TO PERFORM THESE FUNCTIONS DURING THE DAY TIME.

WHEN SETTING UP FOR A VIEWING SESSION, PLACE THE TELESCOPE IN AN AREA SHELTERED FROM THE WIND IF POSSIBLE. THE BEST NIGHT TIME VIEWING WILL BE AWAY FROM CITY LIGHT AND WHEN THE ATMOSPHERE IS "STEADY".

WITH A LITTLE PRACTICE YOU WILL LEARN TO JUDGE WHEN VIEWING CONDITIONS ARE GOOD. LOOK FOR THE NIGHTS WHEN THE STARS SHINE BRIGHTLY WITH LITTLE OR NO TWINKLING.

USE LOW POWER TO TAKE ADVANTAGE OF THE WIDER FIELD OF VIEW AND BRIGHTER IMAGE. RESERVE YOUR HIGHER POWERS FOR THOSE NIGHTS WHEN VIEWING CONDITIONS ALLOW FOR DETAILED OBSERVATIONS.

**IF YOU NEED ANY FURTHER HELP WITH YOUR GALILEO TELESCOPE
PLEASE CALL US @ 305-245-8444 MON-FRI 9AM - 5PM E.S.T
OR E-MAIL US AT CUSTOMERSERVICE@COSMOSOPTICS.COM**

Galileo® Limited One Year Warranty

We guarantee to replace or, at our option, repair any products or parts thereof which are found defective in material or workmanship during the first year from date of purchase. Our obligation with respect to such products or parts shall be limited to replacement or repair. In no event shall we be liable for consequential or special damages or for transportation, installation, adjustment, or other expenses which may arise in connection with such product or parts. The customer shall be responsible for all costs of transportation and insurance, both to and from GALILEO/COSMO BRANDS INC., and shall be required to prepay such costs. No expenses, warranties and implied warranties, whether or not merchantability of fitness for any particular use or otherwise (except as to title) other than these expressly set forth above which are made in writing and signed by executive officer of our corporation.

NO LIABILITY FOR CONSEQUENTIAL DAMAGES, IN NO EVENT SHALL THE MANUFACTURER OR ITS SUPPLIERS BE LIABLE FOR ANY DAMAGES WHATSOEVER. BECAUSE SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF THE POSSIBILITY FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES, THE ABOVE LIMITATION MAY NOT APPLY TO YOU.

Galileo®

COSMO BRANDS INC.

21230 SW 246th ST. REDLAND FL 33031 USA

www.cosmosoptics.com

IF YOU NEED ANY FURTHER HELP WITH YOUR GALILEO TELESCOPE
PLEASE E-MAIL US AT CUSTOMERSERVICE@COSMOOPTICS.COM